

FIELDQUIP®

...a cut above the rest!



SETTING THE STANDARD

TWIGA COMPACT SERIES REACH MOWERS

FRONT MOUNT

TWIGA COMPACT SERIES REACH MOWERS

- 3.6 and 4.6 metre reach options
- 25hp minimum tractor requirement
- 3-point linkage or DIN plate mounting
- Parallel arm geometry
- Fully independent hydraulic system
- 60 litre oil capacity
- Low power requirement
- Hydraulic safety breakout
- Choice of control systems
- Choice of cutting heads and attachments

An industrial grade reach mower, The TWIGA Compact Front Mount has been fitted with an offset pivot position allowing the operator to work in tighter and higher spaces, giving added maneuverability and flexibility in operation.

Ideal for utilising in key applications such as amenity and grounds maintenance contracts, the TWIGA Compact Front Mount now offers a fold flat arm position bringing the machine over for a lower point of clearance to improve visibility.

Available with sideways reach options of 3.6 and 4.6 metres and a choice of additional cutting attachments, this is a compact reach arm that can offer the contractor additional versatility in a competitive marketplace.

Model	Max. Reach	Weight	HP (Min.)	Tractor Weight Req.
TWIGA COMPACT 360 FM	3.6m (11'8")	300 kg	25	1300kg
TWIGA COMPACT 460 FM	4.6m (15'1")	510 kg	40	1300kg



FREECALL: 1800 454 150

**Phone: (07) 4691 1500 Fax: (07) 4691 1511 www.fieldquip.com.au
199 Bridge Street Oakey Queensland Australia 4401**

Additional lines may be added or deleted from the range in this guide -
visit www.fieldquip.com.au for new models and availability