

2150

15' Flex-Wings



Smooth Top and Bottom Deck Design with Dual Cut Chambers



New Composite Divider Shield



Mechanical Level Lift



Infinity Cast Carrier utilizing many of the same drivetrain components as the 3150



5 Year Limited Gearbox Warranty



New Improved Tongue Design featuring Standard Clevis



CAT 5 CV Main & CAT 4 Wing Drivelines



Coil Spring Suspension



Equip your 2150 with Rhino Trax "Foam Filled" tires or any of our 5 great tire options.



LED Lights are Standard Equipment



2150 SPECIFICATIONS

Specifications		2150
Cutting Width		180"
Transport Width		116"
Transport Height		75"
Overall Width		187"
Overall Length		172"
Cutting Height*		2" - 14"
Height Adjustment		Hydraulic Cylinder
Jack Stand		Standard
Hitch		Clevis
Blade Carrier		Infinity
Blades		1/2" x 4" Parallel Lift
Blade Overlap		6"
HP Required (Min)		50 HP
Gearbox Rating**	Divider	160 HP
	Center & Wing	130 HP
Gearbox Oil (85W-140)		Factory Filled
Output Shaft Diameter		2"
Blade Tip Speed (FPM)	Center 540 RPM	14,861 FPM
	1000 RPM	15,570 FPM
	Wing 540 RPM	14,861 FPM
	1000 RPM	15,776 FPM
Cutting Capacity		2 1/2"
Driveline Size	Main	CAT 5 CV
	Wing	CAT 4
Driveline Protection		Slip Clutch
Deck Thickness	Center	10 Ga Top/ 7 Ga Bottom
	Wing	10 Ga Top & Bottom
Side Skirt		1/4" x 12 3/8"
Tire Selections		Rhino Trax, Laminated, Pneumatic, or Foam Filled (4, 6, or 8 tires)
Wing Lift		Mechanical Level Lift
Wing Flex (Degrees)		87° Up/ 25° Down/45° Operational
Tongue Weight		1,430 lbs
Safety Tow Chain		Standard
LED Light Kit		Standard
Safety Deflector		Deflectors, Chains, or Combination
Weight (Approx)***		4,290 lbs (w/ Single Chains & 6 Rhino Trax Tires)

* Cutting Height dependent on tire size

** Gearbox Rating based on field performance

*** Weight Varies with machine configuration



Smooth Top & Bottom Deck



Heavy-Duty Blades
& Infinity Carrier



New Composite Divider Shield